



...the choice matters

Electrosafe MD555  
Earthing Floor matting  
www.matsdirect.co.uk

**ASTM D178 /ANSI JS.7 Type 1 Class 4**

An extremely ultra high specification quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test	50,000v
Surface proof test	40,000v
Working voltage	36,000v



<b>Colour:</b>	Black
<b>Hardness:</b>	60 shore A
<b>Tensile:</b>	5.0 Mp
<b>Elongation</b>	250%
<b>Temperature Range:</b>	-20/+70 DegC
<b>Abrasion Resistance:</b>	2000 mm3

<b>Thickness:</b>	12.5
<b>Roll size (10m x 0.91m):</b>	EX STOCK
<b>Weight/ M2 (kgs - appx):</b>	14.5

**MD555 Electrosafe Matting Performance.**

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

**Cleaning and Maintenance Daily:**

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water. Matting should be air dried, but not such that the matting temperature exceeds 65°C.

**MatsDirect UK Ltd**  
Unit 2 Bolholt Industrial Park  
Walshaw Road  
Bury, Lancashire  
BL8 1PL UK

**For all enquires:**

**Tel:** 0161 797 6785  
**Fax:** 0845 370 6786  
**E-mail:** info@matsdirect.co.uk