



...the choice matters

Electrosafe MD557
Earthing Floor matting

www.matsdirect.co.uk

ASTM D178 /ANSI JS.7 Type 2 Class 2

An extremely ultra high specification quality Neoprene Rubber compound safety matting product able to withstand the following:

- Dielectric test 20,000v
- Surface proof test 10,000v
- Working voltage 7,500v



Colour:	Black	Thickness:	4.5mm
Hardness:	60 shore A	Roll size (10m x .91m):	EX STOCK
Tensile:	5.0 Mp	Thickness:	6.5mm
Elongation	250%	Roll size (10m x .91m):	EX STOCK
Temperature Range:	-20/+70 DegC	Thickness:	10mm
Abrasion Resistance:	200 mm3	Roll size (10m x .91m):	EX STOCK

MD557 Electrosafe Matting Performance.

- Class 5.1.2.1. Ozone resistant
- Class 5.1.2.2. Flame resistant
- Class 5.1.2.3. Oil resistant

Fully branded on reverse.

Extremely safe from electrical shock and hard wearing Positive safe grip from the flutes

Cleaning and Maintenance:

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water.

Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk